



Minutes of the
Dynamic Attachments for Swinging Doors (DASD) Task Group Meeting
via teleconference and *GoToMeeting*
Tuesday, August 18, 2009; 1:00 PM EDT

Call to order. The meeting was called to order at 1:02 PM EDT by Chairman Dave De Block (ODL).

Recording Secretary. John Lewis (NFRC staff) was appointed as recording secretary.

Antitrust. Chair De Block reviewed the NFRC Antitrust guidelines.

Business of the Meeting.

Chair De Block gave an overview of the agenda for the meeting, and that was to review the proposed changes to the NFRC 100 and NFRC 200 to allow these documents to comply with *ENERGY STAR*[®] requirements. He added that it appears the NFRC PCP documents do not require modification as they already allow the half lite door to be labeled using existing methodology.

Chair De Block then reviewed the proposed changes to the NFRC 100 and NFRC 200 document. Changes were made based on comments from the TG and “lite” was the decided spelling for doorglass.

Chair De Block stated that NFRC will need a new label for half-lite doors (a sample label is attached hereto).

Chair De Block requested NFRC staff to ballot the revised sections of NFRC 100 and NFRC 200; J. Lewis was directed to create a 100 and 200 ballot from the sections of the 2 documents revised during this meeting.

Chair De Block plans to petition the NFRC Board of Directors during their next conference call to allow manufacturers to proceed with testing prior to the November 2009 meeting during which it is anticipated these balloted changes would be approved by the membership.

Adjournment.

There being no further business, the call adjourned at 1:16 PM EDT.

Current Label



NFRC DYNAMIC ATTACHMENT RATINGS

ODL, Inc. - Swinging Door Shade/Blind Storm Panel CPD#ODL-K-6 (Interior)

This rating uses reference product energy performance-actual product performance may vary.

ENERGY PERFORMANCE RATING

Reference Product		U-Factor	SHGC	VT
Attachment installed on full light swinging door wood edge steel skin eps core 1/2" IG	BLIND OPEN	0.34	0.34	0.37
	BLIND CLOSED	0.31	0.16	—
Attachment installed on full light swinging door wood edge fiberglass skin urethane core 1/2" IG	BLIND OPEN	0.30	0.34	0.37
	BLIND CLOSED	0.29	0.16	—

Manufacturer stipulates that these ratings conform to NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

www.nfrc.org

Proposed 'Half Lite' Label

insert "1/2 Lite" here



NFRC DYNAMIC ATTACHMENT RATINGS

ODL, Inc. - Swinging Door Shade/Blind Storm Panel
CPD#ODL-K-6 (Interior)

This rating uses reference product energy performance-actual product performance may vary.

ENERGY PERFORMANCE RATING

Reference Product		U-Factor	SHGC	VT
Attachment installed on full light swinging door wood edge steel skin eps core 1/2" IG	BLIND OPEN	0.34	0.34	0.37
	BLIND CLOSED	0.31	0.16	—
Attachment installed on full light swinging door wood edge fiberglass skin urethane core 1/2" IG	BLIND OPEN	0.30	0.34	0.37
	BLIND CLOSED	0.29	0.16	—

Manufacturer stipulates that these ratings conform to NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

www.nfrc.org