


PCP Appendix B - Add attached drawing and rules for use.

**Figure B-XXX**  
**Sample Temporary Label for TDD**

	<p><b>World's Best Tubular Daylighting Company</b></p> <p>Acrylic Dome • Dual Diffuser Glazing Product Type: Tubular Daylighting Device</p>	
<p><b>ENERGY PERFORMANCE RATINGS</b></p>		
<p>U-Factor (U.S./I-P)</p> <p><b>0.50</b>   <b>0.60</b></p> <p>INSULATION @ ROOF   INSULATION @ CEILING</p>	<p>Solar Heat Gain Coefficient</p> <p><b>0.40</b></p>	
<p><b>ADDITIONAL PERFORMANCE RATINGS</b></p>		
<p>—</p>	<p>—</p>	
<p>Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.</p> <p><a href="http://www.nfrc.org">www.nfrc.org</a></p>		

The label shall display ratings in accordance with the following criteria:

- A. TDD label requires specification of insulation location as shown above
- B. “Insulation at roof” value (left); “Insulation at ceiling” value (right)
- C. If product is designed for insulation in only one location, the other location’s placeholder is not required.